

Terminations

Ceramic Band Type P3 – DIN 49458 A/B Quick Disconnect Plugs

Continued from previous page...



One-Piece Band

Standard Termination Location:
opposite the gap; center of width


- * Minimum Inside Diameter: 3" (76.2 mm)
- * Minimum Width: 2" (50.8 mm)

Type P3□—Vertical Box Assembly


- P3A—Box assembly only
- P3B—Box assembly w/straight plug
- P3C—Box assembly w/right-angle plug

Plug Electrical Ratings

- * 2-Pole 3-Wire Grounding
- * Maximum Volts: 250 VAC
- * Maximum Amps: 16A
- * Maximum Temperature: 392°F (200°C)



Standard Pin Orientation



Two-Piece Band

Standard Termination Location:
center of each half; center of width

- * Minimum Inside Diameter: 4" (101.6 mm)
- * Minimum Width: 2" (50.8 mm)

Available on Reverse Band

Consult Tempco with your requirements.

Ceramic Band Type P4 – DIN 49458 A/B Quick Disconnect Plugs



One-Piece Band

Standard Termination Location:
opposite the gap; center of width


- * Minimum Inside Diameter: 2-1/2" (63.5 mm)
- * Minimum Width: 2-1/2" (63.5 mm)

Type P4□—Horizontal Box Assembly


- P4A—Box assembly only
- P4B—Box assembly w/straight plug

Plug Electrical Ratings

- * 2-Pole 3-Wire Grounding
- * Maximum Volts: 250 VAC
- * Maximum Amps: 16A
- * Maximum Temperature: 392°F (200°C)



Standard Pin Orientation



Two-Piece Band

Standard Termination Location:
center of each half; center of width

- * Minimum Inside Diameter: 4" (101.6 mm)
- * Minimum Width: 2-1/2" (63.5 mm)

Available on Reverse Band

Consult Tempco with your requirements.