

## Heated Hose Assemblies

### Electrically Heated Hose Assemblies



#### Design Features

- \* Base Hose has a smooth bore Teflon® core with Stainless Steel overbraid.
- \* Self-vulcanizing Silicone TGL bedding tape at 50% overlap.
- \* Kapton® insulation wrapped stranded nichrome alloy heater element.
- \* 2 layers of 1/8" Nomex® felt insulation.
- \* Layer of 2" wide black tape for final wrap.
- \* Heavy duty abrasive resistant outer covering, polyester braid; optional water resistant jacket is available upon request.
- \* Heat shrink tube end caps.
- \* Male NPT or 37° JIC female swivel fittings are standard; options include Tri-Clamp or Tubing/Pipe for compression fittings. Choice of Stainless Steel or plated carbon steel.
- \* Temperature range to 450°F/232°C.
- \* Overall length up to 600 inches.
- \* Temperature sensors such as thermocouples or RTDs can be built-in to the assembly.
- \* Snap action thermostats can be built in to the assembly to limit the maximum temperature.
- \* 6 ft. power leads standard; length can vary upon request.
- \* Hose assemblies available in 120 and 240 Vac.
- \* Ground connection to the Stainless Steel overbraid.



#### Tempco Control Consoles

Ideal for controlling process temperatures on heated hose assemblies. Complete information can be found on page 13-52.

Tempco's Electrically Heated Hose Assemblies are designed for optimum transfer of non-explosive liquids or gases. Tempco's HEH Transfer Hoses are Teflon® lined stainless steel braid heated flexible assemblies. Style R (regular pressure) or Style H (high pressure) transfer hoses are used in a wide range of applications such as water (freeze protection), steam, wax, plastics and many others. Heated transfer hoses improve fluid transfer for many applications.



#### Typical Applications

- ✦ Hot Melt Systems
- ✦ Petroleum Products
- ✦ Food Products
- ✦ Hot Oil Lines
- ✦ Chemical Transfer
- ✦ Gas Analyzer Systems
- ✦ Steam Transfer
- ✦ Water & Waste Disposal
- ✦ Bulk Transfer
- ✦ Paint Systems
- ✦ Tar & Asphalt
- ✦ Waxes – Candle Making
- ✦ Adhesives

#### Construction Characteristics

Tempco's Heated Transfer Hoses are built to the most stringent standards. Each hose is hand assembled to exact physical and electrical specifications. The heated hose assembly starts with the highest quality Teflon® smooth bore core with Stainless Steel overbraid style hose. Over this is wrapped a layer of self-vulcanizing silicone TGL bedding tape at 50% overlap as a base for the resistance wire. The stranded resistance wire is pre-wrapped with Kapton® insulation before winding around the growing assembly in the precise pattern required for uniform heating. Next is wound two layers of Nomex® felt insulation, to maintain consistent heat and a safe cool-to-the-touch design, followed by a layer of 2" wide black tape. The standard hose outer cover is an abrasion resistant polyester braid for normally dry environments. An optional outer cover can be provided for water resistant protection.

The hose assembly is then finished with heat shrink end caps, specified hydraulic fittings and electrical connectors. Hoses are also manufactured with optional built-in sensors including RTDs or thermocouples.

#### HEH Heated Hose Assembly Length Definition

1. For Heated Hose Assemblies with 37° JIC Female Swivel fittings, the specified Length is defined as fitting seat to seat.
2. For Heated Hose Assemblies with other permanently attached fittings, such as Tri-Clamps, Rigid NPT or Tubing, regardless of fitting type or gender, the specified Length is measured from the outside edge to the outside edge of the fittings.
3. Fitting adapters such as male JIC to male NPT, are not included in the Length specification.
4. Length Tolerances are stated as follows:
  - 17.99" or less: ±0.5"
  - 18" to 36": ±0.75"
  - 3 feet to 10 feet: ±1.0"
  - 10 feet to 20 feet: ±1.5"
  - 20 feet to 50 feet: ±2.5"

**View Product Inventory @ [www.tempco.com](http://www.tempco.com)**

### Specifications for Heated Hose Assemblies

Hose Size	Style R – Regular Pressure		Style H – High Pressure		Max. Rec. Watt Density (w/ft.)		Max. Working Pressure (PSI)		Minimum Bend Radius	Male NPT Fitting Size	JIC Fitting Size, SS
	Core ID	Hose Assembly	Core ID	Hose Assembly	R Style	H Style	R Style	H Style	in. / mm	SS	
	in. / mm	OD in. / mm	in. / mm	OD in. / mm							
#4	.187 / 4.75	1.40 / 35.6	.222 / 5.64	1.40 / 35.6	23	30	2250	4000	4 / 102	¼-18	7/16-20
#6	.312 / 7.92	1.50 / 38.1	.308 / 7.82	1.50 / 38.1	25	40	1875	4000	8 / 203	¾-18	9/16-18
#8	.406 / 10.31	1.59 / 40.4	.401 / 10.19	1.59 / 40.4	30	50	1500	4000	10 / 254	½-14	¾-16
#10	.500 / 12.70	1.69 / 42.9	.495 / 12.57	1.69 / 42.9	35	55	1312	4000	13 / 330	½-14	7/8-14
#12	.625 / 15.87	1.79 / 45.5	.617 / 15.67	1.79 / 45.5	40	65	1125	4000	15 / 381	¾-14	1 1/16-12
#16	.875 / 22.22	2.10 / 53.3	.867 / 22.02	2.30 / 58.4	50	85	750	4000	18 / 457	1-11½	1 5/16-12
#20	1.12 / 28.57	2.60 / 66.0	1.118 / 28.40	2.70 / 68.6	65	95	500	4000	24 / 610	1 1/4-11½	1 5/8-12



**Notes:** Operating pressures are for non-impulsive applications only.

#20 and High Pressure can only be done for special applications, consult Tempco.

### Ordering Code:

HEH - 1 2 3 4 5 6 7 8 9 10 11

#### Hose Style BOX 1

**R** = Regular Pressure, Teflon®  
**H** = High Pressure, Teflon®  
**X** = Other

#### Length BOX 2

In 6" increments  
 From **006** to **600** inches

#### Trade Size BOX 3

**04, 06, 08, 10, 12, 16, 20**  
**XX** = Other

#### Wattage BOX 4

Insert Required Wattage  
 Example: **0120** = 120 Watts



**Note:** Larger wattages are limited to 240V due to overall amperage requirements.

#### Voltage BOX 5

**1** = 120 Vac  
**2** = 240 Vac  
**3** = 208 Vac  
**4** = 277 Vac  
**X** = Other



**Note:** It is strongly recommended that a sensor and separate temperature control or a thermostat be used to control the temperature of Tempco's Heated Hose Assemblies. It is very difficult to limit the overall temperature by using a lower wattage and have a reasonable rise time.

#### Electrical Connectors BOX 6

**A** = Hubbell® #4720C, 15A, 120 Vac, locking plug (NEMA L5-15P)  
**B** = Hubbell® #4570C, 15A, 240 Vac, locking plug (NEMA L6-15P)  
**C** = Industry common, 9-pin Amp® connector  
**D** = No connector, flying leads  
**E** = Standard straight blade, 15A, 120 Vac, (NEMA 5-15P)  
**F** = Standard straight blade, 15A, 240 Vac, (NEMA 6-15P)  
**X** = Other

#### Temperature Sensor BOX 7

**N** = None  
**A** = RTD, 100 ohms, platinum, 2-wire, leads only  
**B** = Thermocouple, Type J, leads only  
**C** = Thermocouple, Type K, leads only  
**D** = RTD, 100 ohms, platinum, 3-wire, leads only  
**F** = Thermocouple, Type J, Std. Plug  
**G** = Thermocouple, Type K, Std. Plug  
**M** = Thermocouple, Type J, Mini-Plug  
**P** = Thermocouple, Type K, Mini-Plug  
**X** = Other

#### Hydraulic Fitting – Near Electrical Connection BOX 8

**J** = JIC 37° Female Swivel  
**N** = JIC 37° Female Swivel and Male NPT adapter  
**Optional**  
**T** = Tri-Clamp  
**P** = Tubing / Pipe (for compression fitting)  
**X** = Other

#### Hydraulic Fitting – Opposite End BOX 9

**J** = JIC 37° Female Swivel  
**N** = JIC 37° Female Swivel and Male NPT adapter  
**Optional for Style R only:**  
**T** = Tri-Clamp  
**P** = Tubing / Pipe (for compression fitting)  
**Optional:**  
**X** = Other

#### Hydraulic Fitting Material BOX 10

**S** = Stainless Steel  
**X** = Other

#### External Covering BOX 11

**P** = Heavy duty polyester braid  
**Optional**  
**N** = Water resistant jacket (Available for limited sizes; consult Tempco)  
**X** = Other

### Ordering Information

**Heated Hose Assemblies** are offered with the features listed above. Create an ordering code by filling in the boxes with the appropriate number and/or letter designation for your requirements and a part number will be assigned.

*Consult Tempco with your requirements.*

**Standard lead time is 2 to 3 weeks.**

#### Accessory Item (Optional)

9-pin mating connectors, includes 12" of pre-attached leads to crimp sockets and cable clamp/strain relief.

Part Number	Mounting	Heated Hose Sensor Type
EHDR-1115	Cable	Type J thermocouple
EHDR-1207	Cable	Type K thermocouple
EHDR-1208	Cable	2 or 3 wire RTD temperature sensor
EHDR-1209	Panel	Type K thermocouple
EHDR-1210	Panel	2 or 3 wire RTD temperature sensor