

## Model TEC-9400 1/16 DIN Temperature Controller



### Design Features

- \* 1/16 DIN size – 48 mm × 48 mm
- \* Fuzzy modified PID heat and cool control
- \* Universal input (TC, PT100, mA, V) with high accuracy 18-bit D-A
- \* Countdown display
- \* RS - 485 and Analog Retransmission Available
- \* Micro USB Programming Port
- \* Fast sampling rate (200 msec)
- \* Manual control & auto-tune function
- \* Wide range of alarm mode selection
- \* Lockout protection
- \* Bumpless transfer during failure mode
- \* Soft-start ramp & dwell timer
- \* Bright LCD display stabilized with digital filter
- \* High performance with low cost

### Agency Approvals:



RoHS, REACH, WEEE

**Hardware Code:** TEC-9400 - 1 2 3 4 5 6 7 8

A Part Number based on the hardware code and any software pre-programming will be issued at time of order.

**Standard lead time is stock to 2 weeks.**

#### Power Input BOX

- 4 = 90-250 VAC
- 5 = 11-40 VDC / 20-28 VAC

#### Output 1 BOX 2

- 1 = Relay: 2A / 240 VAC
- 2 = Pulse DC for SSR drive: 5 VDC (30 mA max)
- 3 = Isolated, 4-20 mA (default), 0-20 mA
- 5 = Isolated VDC, 0-10 scalable
- C = Pulse DC for SSR drive: 14 VDC (40 mA max)

#### Output 2 / Alarm 1 BOX 3

- 0 = None
- 1 = Relay: 2A / 240 VAC
- 2 = Pulse DC for SSR drive: 5 VDC (30 mA max)
- 3 = Isolated, 4-20 mA (default), 0-20 mA
- 5 = Isolated, VDC, 0-10 scalable
- C = Pulse DC for SSR drive: 14 VDC (40 mA max)

#### Alarm 2 BOX 4

- 0 = None
- 1 = Relay: 2A / 240 VAC

#### Option 1 BOX 5

- 0 = None
- 1 = RS-485 Interface

#### Option 2 BOX 6

- 0 = None
- 1 = 2 Event Inputs
- 2 = 1 Event Input and 1 CT Input
- 3 = 2 CT Inputs

#### Option 3 BOX 7

- 0 = None
- 1 = Retransmit: 4-20 mA / 0-20 mA
- 2 = Retransmit: 0-10 VDC
- 3 = Relay: 2A / 240 VAC

#### Option 4 BOX 8

- 0 = None
- 1 = Terminal Cover



**Note:** Detailed information on features common to digital microprocessor-based TEC temperature controls and the complete Table of Input Range and Accuracy can be found on page 13-46.

#### Transformer for Heater Break Alarm

(0-50 Amp current)

**Part Number: TEC99998**

Specifications on page 13-47



### Power Input

**Standard:** 90-250 VAC, 47-63 Hz; 10 VA, 5W max.  
**Optional:** 11-40 VDC / 20 to 28 VAC, 47-63 Hz; 10 VA, 5W max.

### Signal Input

**Resolution:** 18 bits  
**Sampling Rate:** 5 Times / Second (200msec)  
**Maximum Rating:** -2VDC minimum, 12VDC maximum  
**Sensor Break Detection:** Sensor open for Thermocouple and RTD inputs, sensor short for RTD input, below 1mA for 4-20mA input, below 0.25V for 1-5V input, not available for other inputs  
**Sensor Break Response Time:** Within 4 seconds for Thermocouple and RTD inputs, 0.1 second for 4-20mA and 1-5V inputs

### Event Input

**Number of Event Inputs:** 2  
**Logic Low:** -10V minimum, 0.8V maximum  
**Logic High:** 2V minimum, 10V maximum

### CT Input

**CT Type:** CT98-1  
**Accuracy:** ±2% of Full Scale Reading, ± 1 digit maximum  
**Input Impedance:** 294Ω  
**Measurement Range:** 0-50A AC  
**Output of CT:** 0-5V DC  
**CT Mounting:** Wall (Screw) Mount  
**Sampling Rate:** 1 Time/Second

### Output 1 / Output 2

**Relay Rating:** 2A, 240V AC, 200000 Life Cycles for Resistive Load  
**Pulsed Voltage:** Source Voltage 5V, Current Limiting Resistance 66Ω  
**Linear Output Resolution:** 15 Bits  
**Isolation Breakdown Voltage:** 1000 V AC  
**Load Capacity of Linear Output:** Linear Current: 500Ω maximum, Linear Voltage: 10KΩ minimum

### Alarm

**Maximum Rating:** 2A, 240VAC, 200000 Life cycles for resistive load  
**Alarm Functions:** Dwell Timer, Deviation Low, Deviation High, Deviation Band Low, Deviation Band High, Process High, Process Low  
**Alarm Mode:** Latching, Hold, Normal, Latching/Hold  
**Dwell Timer:** 0.1 to 4553.6 Minutes

### Data Communications

**Interface:** RS-485  
**Address:** 1-247  
**Parity Bit:** None, Even or Odd  
**Data Length:** 7 or 8 Bits  
**Protocol:** Modbus RTU  
**Baud Rate:** 2.8 - 115.2 Kbits/sec  
**Stop Bit:** 1 or 2 Bits  
**Communication Buffer:** 160 bytes

### Analog Retransmission

**Output Signal:** 4-20 mA, 0-20 mA, 0-10V  
**Resolution:** 15 Bits  
**Accuracy:** ±0.05% of span ± 0.0025% / °C  
**Load Resistance:** 0-500Ω for current output, 10KΩ minimum for voltage output  
**Isolation Breakdown:** 1000VAC minimum  
**Integral Linearity Error:** ±0.005% of span  
**Linear Output Ranges:** 0-22.2mA (0-20mA / 4-20mA), 0-5.55V (0-5V, 1-5V), 0-11.1V (0-10V)

### User Interface

**Keypad:** 4 Keys  
**Display Type:** 4 digit LCD display  
**No. of Display:** 2  
**Upper Display Size:** 0.58" (15mm)  
**Lower Display Size:** 0.3" (7.8mm)

### Programming Port

**Interface:** Micro USB  
**PC Communication Function:** Automatic Setup, Calibration and Firmware Upgrade

### Control Mode

**Output 1:** Reverse (Heating) or Direct (Cooling) Action  
**Output 2:** PID cooling control, Cooling P band 50~300% of PB, Dead band -36.0 ~ 36.0 % of PB  
**ON-OFF:** 0.1-90.0 (°F) hysteresis control (P band = 0)  
**P or PD:** 0-100.0 % offset adjustment  
**PID:** Fuzzy logic modified Proportional band 0.1 ~ 900.0°F, Integral time 0~3600 seconds, Derivative time 0-360.0 seconds  
**Cycle Time:** 0.1-90.0 seconds  
**Manual Control:** Heat (MV1) and Cool (MV2)  
**Failure Mode:** Auto transfer to manual mode while sensor break or A-D Converter damage  
**Ramping Control:** 0 to 900.0°F / Minute or 0 to 900.0°F / Hour Ramp Rate

### Environmental and Physical Specifications

**Operating Temperature:** -10°C to 50°C  
**Storage Temperature:** -40°C to 60°C  
**Humidity:** 0 to 90 % RH (Non-Condensing)  
**Insulation Resistance:** 20MΩ minimum (@500V DC)  
**Dielectric Strength:** 2000V AC, 50/60 Hz for 1 Minute  
**Vibration Resistance:** 10 to 55 Hz, 10m/s<sup>2</sup> for 2 Hours  
**Shock Resistance:** 200 m / s<sup>2</sup> (20g)  
**Moldings:** Flame retardant polycarbonate  
**Mounting:** Panel  
**Dimensions H x W x D:** 1-7/8 x 1-7/8 x 2-3/8" (48 x 48 x 59 mm)  
**Depth Behind Panel:** 2" (50 mm)  
**Cut Out Dimensions:** 1-25/32 x 1-25/32" (45 x 45 mm)  
**Weight:** .35 lbs. (160 g)

### Stock and Common Part Numbers

(All Stock Part Numbers Include Terminal Covers)  
 (Default Type "J" Thermocouple Input)

Part Number	Output 1	Out 2/ Alm 1	Option 1
TEC19001	Relay	None	None
TEC19002	Relay	Relay	None
TEC19003	Relay	Relay	Relay
TEC19004	Pulse DC	None	None
TEC19005	Pulse DC	Relay	None
TEC19006	Pulse DC	Relay	Relay
TEC19007	4-20mA	none	none
TEC19008	4-20mA	Relay	Relay

### Rear Terminal Connections

