

### Quick Disconnect Plugs: Type P1, Type P2, Type P3 and Type P4

Available on any construction or clamping variation. These plug assemblies are highly recommended & should be used whenever possible. The combination of plug & cup assembly along with armor cable covered leads eliminates all live exposed terminals or wiring that can be a potential hazard to employees or machinery.

Type P1 and P3 assemblies are available with a straight or right-

angle plug. Type P2 and P4 plug assemblies have a lower profile and are available with a straight plug only.

To simplify installation, band heaters with these assemblies can be supplied pre-wired, using high temperature lead wires.

The standard leads are 10" of armor cable over 12" of flexible leads. *If longer leads are required, specify when ordering.*

### Duraband® Type P1 – Quick Disconnect Plugs

#### Type P1 □

**P1K** – Cup assembly only

**P1L** – w/straight plug only

**P1M** – w/90° plug only

**P1N** – w/str. plug & galvanized cable



**P1O** – w/str. plug & SS cable

**P1P** – w/str. plug & wire braid

**P1Q** – w/90° plug & galvanized cable

**P1R** – w/90° plug & SS cable

**P1S** – w/90° plug & wire braid



#### Plug Electrical Ratings

- \* 2-Pole 3-Wire Grounding
- \* Maximum Volts: 250 VAC
- \* Maximum Amps: 16A
- \* Maximum Temperature: 392°F (200°C)

#### One-Piece Band

**Standard Termination Location:**  
next to gap; center of width

- \* **Minimum Inside Diameter:** 2" (50.8 mm)
- \* **Minimum Width:** 1-1/2" (38.1 mm)  
If width is between 1-1/2" and 2",  
minimum diameter is 5-1/2".  
If width is greater than 2", minimum  
diameter is 2".



Type P1Q shown



#### Two-Piece Band

**Standard Termination Location:**  
next to same gap on each half;  
center of width

- \* **Minimum Inside Diameter:** 2" (50.8 mm)
- \* **Minimum Width:** 1-1/2" (38.1)  
If width is between 1-1/2" and 2",  
minimum diameter is 5-1/2".  
If width is greater than 2", minimum  
diameter is 2".



#### One-Piece Expandable Band

**Standard Termination Location:**  
next to gap; center of width

- \* **Minimum Inside Diameter:**  
2-1/2" (63.5 mm)
- \* **Minimum Width:** 1-1/2" (38.1 mm)  
If width is between 1-1/2" and 2",  
minimum diameter is 5-1/2".  
If width is greater than 2", minimum  
diameter is 2".

