# **Industrial Process Heaters**

#### **Drum Heaters**



## Speed Flow of Solid and Semi-Solid Viscous Materials with Tempco Electric Drum and Pail Heaters

Typical Drum Heater with Infinite/Variable Control

Optional Drip Guard
Prevents contamination of the heater from drum materials.
Available for 55 gallon drums only.





# Standard (Non-Stock) and Stock Sizes Stock Items Are Shown In RED

	Drum Size	Temp Control	Watts	Volts	Part Number
	55 GAL. 22.5" Diameter	Infinite/Variable Heat Control 60°-250°F Thermostat 200°-400°F Thermostat	1750 1920 1920	120	DHM00010 DHM00020† DHM00030†
		Infinite/Variable Heat Control 60°-250°F Thermostat 200°-400°F Thermostat	3000	240	DHM00030 DHM00010†† DHM000
	30 GAL. 18.5" Diameter	Infinite/Variable Heat Control 60°-250°F Thermostat 200°-400°F Thermostat	1750 1920 1920	120	DHP 100080 D AND 90† HM001 9†
	16 GAL. 14.5" Diameter	Infinite/Variable Heat Control 60°-250°F Thermostat 200°-400°F Thermostat	1500	120	DA (00120 DHN )0130
	5 GAL. 11.25" Diameter	Infinite/Variable Heat Control 60°-250°F Thermostat 200°-400°F Thermostat	200	120	DHM00140 DHM00150 DHM00160

#### **Design Features**

- \* Rapid heat-up of drum
  - \* Easy installation and removal
  - \* Durable metal design
    - \* Infinite switch or thermostat
      - \* 3-heat control
      - \* Indicator lamps: green for power, red for heater
        - \* 6 ft. power cord
          - \* Variety of diameters (all 5" wide) and ratings
            - \* Stock to 2 week lead time!
              - \* UL listed and CSA cer Ged

**Thermostat Control** models cause to perature in an area remote from the heating element and will automatically cycle heater to praint in settemp rature. Three-heat switch allows three we tage ratings per thermostat setting and voltage ratings.

Infinite/Variable Con Conodels cycle the current ON and OP of The ratio of ON time will increase as the control of advaced three-heat switch allows the operator to control of neater output within a given 3 settings of him medium, or low.

#### Standard lead time is Stock to 2 weeks.

- † The 1920 Watt/120V model is equipped with a special high amperage plug. If required the matching receptacle is: Part Number EHD-103-108 (Hubbell\* #5361, 20A, 125V)
- †† The 3000 Watt/240V is equipped with a standard 15A/240V straight blade type plug.

### **Typical Applications**

Indust	Applications	Industries	Applications
Mining Oil Compa	7 0 7	Farm Supply Distributors	Heat tallow to 140°F to mix with feed ration
Candle Magers	Heat wax to make candles	Beekeepers	Reliquefy honey after crystallizing
Food Proces rs	Heat food additives	Roofers	Heat roofing material during cold weather
Aircraft Mechanic	Heat aircraft grease during cold weather	Chemical Manufacturers	Heat chemical components
Auto Mechanics Undercoaters	Accelerate flow of undercoating material		During the manufacturing process Heat adhesives

### Stock Heated Drum Dolly for Metal Drums



Holds up to 900 lbs.

# Chain Link Reinforced Power Cord Infinite Variable Heat Control

Heat your 55 gallon drum while keeping it portable. Just place the drum on the dolly's 3/4" thick  $\times$  15-1/4" square heated platen.

The overall diameter is 28-1/2" with an inside diameter of 24". The dolly comes equipped with 3" diameter phenolic casters and a 6 foot long cord and plug.

Part Number: **DHM01001** 1750 Watts, 120VAC Part Number: **DHM01002** 1920 Watts, 240VAC

View Product Inventory @ www.tempco.com