

## Terminations

### Ceramic Band Type P3 – DIN 49458 A/B Quick Disconnect Plugs

Continued from previous page...



#### One-Piece Band

**Standard Termination Location:**  
opposite the gap; center of width


- \* **Minimum Inside Diameter:** 3" (76.2 mm)
- \* **Minimum Width:** 2" (50.8 mm)

#### Type P3 □ – Vertical Box Assembly


- P3A**—Box assembly only
- P3B**—Box assembly w/straight plug
- P3C**—Box assembly w/right-angle plug

#### Plug Electrical Ratings

- \* **2-Pole 3-Wire Grounding**
- \* **Maximum Volts:** 250 VAC
- \* **Maximum Amps:** 16A
- \* **Maximum Temperature:** 392°F (200°C)



**Standard Pin Orientation**



#### Two-Piece Band

**Standard Termination Location:**  
center of each half; center of width

- \* **Minimum Inside Diameter:** 4" (101.6 mm)
- \* **Minimum Width:** 2" (50.8 mm)

**Available on Reverse Band**

*Consult Tempco with your requirements.*

### Ceramic Band Type P4 – DIN 49458 A/B Quick Disconnect Plugs



#### One-Piece Band

**Standard Termination Location:**  
opposite the gap; center of width

- \* **Minimum Inside Diameter:** 2-1/2" (63.5 mm)
- \* **Minimum Width:** 2-1/2" (63.5 mm)

#### Type P4 □ – Horizontal Box Assembly


- P4A**—Box assembly only
- P4B**—Box assembly w/straight plug

#### Plug Electrical Ratings

- \* **2-Pole 3-Wire Grounding**
- \* **Maximum Volts:** 250 VAC
- \* **Maximum Amps:** 16A
- \* **Maximum Temperature:** 392°F (200°C)



**Standard Pin Orientation**



#### Two-Piece Band

**Standard Termination Location:**  
center of each half; center of width

- \* **Minimum Inside Diameter:** 4" (101.6 mm)
- \* **Minimum Width:** 2-1/2" (63.5 mm)

**Available on Reverse Band**

*Consult Tempco with your requirements.*