




PCM-1000 Series Pre-Wired Power Control Boxes (NEMA 12 Indoor Use)



16 Amp Rating

- * TEC-9400 PID temperature control with bright LCD Display using NFPA/IEC standard colors
- * Standard size thermocouple jack
- * 5-foot, 3-conductor line cord
- * 20A straight-blade heater receptacle with ground
- * Fused at 20A
- * 25A mechanical relay
- * Enclosure Dimensions: 6"H x 6"W x 6"D
- * Wall mounting slots: 4" centers side to side, 6-3/4" centers top to bottom
- * Agency Approval:  File #: E307875

Part Number PCM10076

- * Voltage: 120 VAC (1 Phase)
- * Maximum Wattage: 1920 W
- * Temperature Range: 0-1200°F
- * Type J thermocouple jack

Part Number PCM10077

- * Voltage: 240 VAC (1 Phase)
- * Maximum Wattage: 3840 W
- * Temperature Range: 0-1200°F
- * Type J thermocouple jack

Part Number PCM10078

- * Voltage: 120 VAC (1 Phase)
- * Maximum Wattage: 1920 W
- * Temperature Range: 0-2400°F
- * Type K thermocouple jack


Part Number PCM10079

- * Voltage: 240 VAC (1 Phase)
- * Maximum Wattage: 3840 W
- * Temperature Range: 0-2400°F
- * Type K thermocouple jack

24 Amp Rating



- * Temperature Range: 0-2400°F
- * TEC-9400 PID temperature control with bright LCD Display using NFPA/IEC standard colors
- * NO-NC alarm contacts
- * Terminal blocks for incoming power, heater power and universal sensor

- * 32A magnetic contactor
- * BX connectors for sensor, incoming & heater leads
- * Disconnect & 30A heater fusing to be supplied by customer
- * Agency Approval:  File #: E307875

Part Number PCM10080

- * Voltage: 240 VAC (1 or 3 Phase)
- * Maximum Wattage: 5760 or 9970 W
- * Enclosure Dimensions: 10"H x 10"W x 6"D
- * Wall mounting slots: 8" centers side to side, 10-3/4" centers top to bottom


Part Number PCM10081

- * Voltage: 480 VAC (1 or 3 Phase)
- * Maximum Wattage: 11,520 or 19,930 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom

48 Amp Rating



- * Temperature Range: 0-2400°F
- * TEC-9400 PID temperature control with bright LCD Display using NFPA/IEC standard colors
- * NO-NC alarm contacts
- * Terminal blocks for incoming power, heater power and universal sensor

- * 65A magnetic contactor
- * BX connectors for sensor, incoming & heater leads
- * Disconnect & 60A heater fusing to be supplied by customer
- * Agency Approval:  File #: E307875

Part Number PCM10082

- * Voltage: 240 VAC (1 or 3 Phase)
- * Maximum Wattage: 11,520 or 19,930 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom

Part Number PCM10083

- * Voltage: 480 VAC (1 or 3 Phase)
- * Maximum Wattage: 23,000 or 39,900 W
- * Enclosure Dimensions: 14"H x 12"W x 6"D
- * Wall mounting slots: 10" centers side to side, 14-3/4" centers top to bottom