



Mightyband™ Coil Heaters

Standard (Non-Stock) Round Cable Heaters

Standard Cable Heaters have 304 Stainless Steel Sheath

Inside Diameter		Outside Diameter		Width		Watts	Volts	Distributed Wattage	Close Wound	Lead Protection	Lead Orientation	Part Number
in	mm	in	mm	in	mm							
7/8	22.2	1.115	28.3	2	50.8	670	120		yes	B3	LO2	MHC00045
7/8	22.2	1.125	28.6	2	50.8	670	240		yes	B1	LO2	MHC00046
7/8	22.2	1.125	28.6	2 1/2	63.5	670	240	yes		B1	LO2	MHC00047
7/8	22.2	1.125	28.6	3 3/8	79.4	670	240	yes		B1	LO2	MHC00048
❖ 7/8	22.2	1.181	30.0	2 1/2	63.5	450	240	yes		C1	LO2	MHC00049
7/8	22.2	1.181	30.0	3 3/8	92.1	550	240	yes		C1	LO2	MHC00050
7/8	22.2	1.181	30.0	4 3/16	109.5	550	240	yes		C1	LO2	MHC00051
7/8	22.2	1.181	30.0	5 1/16	134.9	650	240	yes		C1	LO2	MHC00052
7/8	22.2	1.181	30.0	6 3/16	160.3	650	240	yes		C1	LO2	MHC00053
7/8	22.2	1.181	30.0	7 1/16	185.7	650	240	yes		C1	LO2	MHC00054
❖ 7/8	22.2	1.125	28.6	3	76.2	680	240	yes		C1	LO2	MHC00055
❖ 7/8	22.2	1.125	28.6	3 1/2	88.9	700	240	yes		C1	LO2	MHC00056
7/8	22.2	1.125	28.6	3 3/8	92.1	770	240	yes		B1	LO2	MHC00057
7/8	22.2	1.125	28.6	4 3/16	109.5	770	240	yes		B1	LO2	MHC00058
7/8	22.2	1.125	28.6	5 1/16	134.9	770	240	yes		B1	LO2	MHC00059
7/8	22.2	1.125	28.6	4	101.6	775	240	yes		C1	LO2	MHC00060
7/8	22.2	1.125	28.6	6 3/16	160.3	730	240	yes		B1	LO2	MHC00061
7/8	22.2	1.125	28.6	7 1/16	185.7	730	240	yes		B1	LO2	MHC00062
❖ 7/8	22.2	1.125	28.6	5	127.0	900	240	yes		C1	LO2	MHC00063
7/8	22.2	1.105	28.1	8 5/16	211.1	730	240	yes		C1	LO2	MHC00064
7/8	22.2	1.105	28.1	9 3/16	236.5	730	240	yes		C1	LO2	MHC00065
7/8	22.2	1.105	28.1	10 3/16	261.9	730	240	yes		C1	LO2	MHC00066
❖ 7/8	22.2	1.125	28.6	6	152.4	1000	240	yes		C1	LO2	MHC00067
7/8	22.2	1.105	28.1	11 3/16	287.3	850	240	yes		C1	LO2	MHC00068
7/8	22.2	1.105	28.1	12 3/16	312.7	850	240	yes		C1	LO2	MHC00069
7/8	22.2	1.105	28.1	13 3/16	338.1	850	240	yes		C1	LO2	MHC00070
7/8	22.2	1.105	28.1	14 3/16	363.5	850	240	yes		C1	LO2	MHC00071
7/8	22.2	1.105	28.6	7	177.8	1100	240	yes		C1	LO2	MHC00072
1	25.4	1.250	31.8	1 1/2	38.1	375	120		yes	B1	LO1	MHC00073
1	25.4	1.306	33.2	1 1/2	38.1	375	240		yes	B1	LO1	MHC00074
1	25.4	1.240	31.5	2	50.8	400	120		yes	B1	LO1	MHC00075
1	25.4	1.266	32.2	2 1/2	63.5	450	120		yes	B1	LO1	MHC00076
1	25.4	1.250	31.8	8	203.2	1250	240		yes	B3	LO1	MHC00077
1 1/4	31.8	1.556	39.5	1	25.4	340	240		yes	B1	LO1	MHC00078
1 1/4	31.8	1.556	39.5	1 1/4	31.8	375	120		yes	B1	LO1	MHC00079
1 1/4	31.8	1.480	37.6	1 1/2	38.1	400	120		yes	B1	LO1	MHC00080
1 1/4	31.8	1.492	37.9	2	50.8	475	120		yes	B1	LO1	MHC00081
1 1/4	31.8	1.480	37.6	2 1/2	63.5	750	240		yes	C1	LO2	MHC00082
1 1/4	31.8	1.514	38.5	4 1/2	114.3	1250	240		yes	C3	LO2	MHC00083
1 1/4	31.8	1.534	39.0	6 1/2	165.1	1800	240		yes	C3	LO2	MHC00084
1 1/4	31.8	1.548	39.3	7	177.8	2000	240		yes	B3	LO1	MHC00085
1 1/4	31.8	1.594	40.5	8 1/2	215.9	2335	240		yes	C3	LO2	MHC00086
1 1/4	31.8	1.626	41.3	10 1/2	266.7	2500	240		yes	C1	LO2	MHC00087



Note: ❖ Denotes the Thermocouple Junction is located between third and fourth coil from the tip end, isolated from the sheath. See page 5-5 for Lead Protection and page 5-4 for Lead Orientation descriptions.

Ordering Information

See page 5-9

CONTINUED