

Closed Cell Elastomeric Thermal Insulation

Design Features

- * *Cost Effective*
- * *Easy to install*
- * *Suitable for wide variety of environments, such as outdoor use and food service*
- * *Temperatures to 257°F (125°C)*
- * *UV resistant*
- * *Fiber Free*

Specifications

Material: 3/4" (19mm) thick closed-cell and lightweight EPDM based elastomeric material

Exposure Temperature Range: -297°F through 257°F

R-value: 3

Density: 3 to 6 Lbs/ft³

Water vapor permeability: 0.10 perm-in (0.15 x 10⁻¹²)

Water absorption (weight %): Less than 5%

Flammability: UL-94 5 V-A. V-O



Sheet Width in (mm)	Sheet Length ft (m)	Description	Part Number
11 (279)	50 (15.2)	Installs around 2.5" O.D. Pipes and smaller	HTP90050
15 (381)	50 (15.2)	Installs around 4" O.D. Pipes and smaller	HTP90051
48 (1219)	25 (7.6)	Installs around vessels and large diameter pipes	HTP90052

FOIL TAPE

Adhesive aluminum tape for extra environmental protection.
Up to 300°F (149°C).

Description	Part Number
3" (76mm) x 180 ft. (55m) roll. To protect insulation from environmental damage.	HTP90055



SEAM-SEALING TAPE

Adhesive tape required for sealing seams.
Up to 180°F (82°C).

Description in (mm)	Part Number
2" (51mm) x 82 ft. (25m) roll. Ideal for pipes and small vessels.	HTP90053
3" (76mm) x 82 ft. (25m) roll. Ideal for large vessels.	HTP90054

