

Constant Wattage Heat Trace Cable

FE Style Heating Cable Maximum Temperature: 400°F (204°C)

The FE Style cable heating element is tension wrapped and covered with a fluorocarbon film and enclosed in a minimum 20 mm Teflon® FEP abrasion resistant extruded jacket. This tough outer cover provides moisture and dielectric protection as well as resistance to abrasion. A layer of tinned copper braid is then applied to meet NEC code and to provide mechanical protection as well as a low resistance to ground.



Design Features

- * **Temperature Exposure Rating 400°F (204°C)**
- * **Ease of installation—cut to length at the job site**
- * **Moisture and chemical resistant**
- * **Stands up to repeated handling and flexing**
- * **Field proven industrial grade construction**
- * **Single end power connection**

Typical Applications

- ✦ **Mid-Temperature Control**
- ✦ **Food Processing Plants**
- ✦ **Freeze Protection**
- ✦ **Chemical Processing Plants**
- ✦ **Hazardous Locations**
- ✦ **Water Lines/Condensate Return Lines**

Specifications

- Voltages Available:** 120, 208, 240, 480V
- Wattages:** 3, 5, 8, 12 (W/ft.)
- Outside Dimensions:** Nom. .300" x .200"
- Exposure Rating:** 400°F (204°C)
- De-Energized:** 450°F (232°C)
- Standard Metal Overbraid:** Tinned Copper (Optional Stainless Steel)
- Moisture and Chemical Resistance:** Excellent
- Flame Resistance:** Outstanding
- Radiation Resistance:** Fair to Good

Agency Approvals

- * **Factory Mutual**
Ordinary Locations
Hazardous Locations:
Class I, Division 2, Groups B, C & D
Class II, Division 2, Groups E, F & G
Class III, Division 2
- * **CSA (120 and 240 VAC only)**
Ordinary Locations
Hazardous Locations:
Class I, Division 2, Groups B, C & D
Class II, Division 2, Groups F & G
Class III, Division 2



Ordering Information

Tempco's FE Constant Wattage Heat Trace Cable is sold by part number and length. The cable part number is put together as follows:

H T P 0 2

Wattage—watts/ft.

- 3 W/ft. = 3
- 5 W/ft. = 5
- 8 W/ft. = 8
- 12 W/ft. = 2

Voltage

- 120 VAC = 1
- 240 VAC = 2
- 208 VAC = 3
- 480 VAC = 4

Outer Layer

- 0 = Standard Tinned Copper Braid
- 3 = Stainless Steel Braid



Note: Due to code requirements, FE cable has a metal overbraid.

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

(800) 323-6859 • Email: sales@tempco.com