



Series CRL E-Mitter Panel Arrays Standard Style ARA Structural Housing Dimensions

A) The Number of Rows will determine the Housing Width. For overall width add 1.50" (for the mounting lips).
B) The Number of Columns will determine the Housing Length. For overall length add 1.50" (for the mounting lips).

Number of Rows	Number of Columns				
	1 W x L	2 W x L	3 W x L	4 W x L	5 W x L
1	5 x 12.5	5 x 24.5	5 x 36.5	5 x 48.5	5 x 60.5
2	9 x 12.5	9 x 24.5	9 x 36.5	9 x 48.5	9 x 60.5
3	13 x 12.5	13 x 24.5	13 x 36.5	13 x 48.5	13 x 60.5
4	17 x 12.5	17 x 24.5	17 x 36.5	17 x 48.5	17 x 60.5
5	21 x 12.5	21 x 24.5	21 x 36.5	21 x 48.5	21 x 60.5
6	25 x 12.5	25 x 24.5	25 x 36.5	25 x 48.5	25 x 60.5
7	29 x 12.5	29 x 24.5	29 x 36.5	29 x 48.5	—
8	33 x 12.5	33 x 24.5	33 x 36.5	—	—
9	37 x 12.5	37 x 24.5	37 x 36.5	—	—
10	41 x 12.5	41 x 24.5	41 x 36.5	—	—
11	45 x 12.5	45 x 24.5	45 x 36.5	—	—
12	49 x 12.5	49 x 24.5	—	—	—
13	53 x 12.5	53 x 24.5	Dimensions are in inches		
14	57 x 12.5	57 x 24.5			
15	61 x 12.5	61 x 24.5	—	—	—



Note: Structural Housing Dimensions (width x length) are in inches. For overall dimensions add 0.75" per side for the mounting lip.



CRL E-Mitter (95 x 295 mm)

Custom Engineered/Manufactured Panels

- Multiple panels are used for larger arrays.
- Consult factory for larger panels not shown in table or custom panels with other spacings. Minimum spacing for CRL heaters is 4.00" x 12.00".
- Special narrow panels having a maximum 30 rows x 1 or 2 columns, & up to 6 rows x 9 columns can be made on special order (max. housing size 121" x 25").

**Consult us with your requirements
There is no substitute for our experience.**

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.