




Series CRL Curved Face Ceramic E-Mitters – Size: 95 mm × 295 mm (3.74" × 11.61")



Color shown is rose (cold) to grey (hot)

Optional Features

- * *Additional Power or Thermocouple Lead Lengths (page 7-23)*
- * *Two-Piece Wave Mounting Clip (page 7-14)*
- * *Reflectors and Other Accessories (pages 7-20 through 7-23)*
- * *Arrays and Power/Temperature Control Panels (start on page 7-15)*

Standard (Non-Stock) CRL E-Mitters

E-Mitters listed have 6" ceramic bead insulated leads, #8-10 spade terminals, and one-piece spring clips for mounting in 20 or 22 gauge sheet metal.

Wattage	Voltage	Color	Watt Density*		Heater Body Temp.**		Peak Emitted Wavelength***	Part Number		
			(W/in ²)	(W/cm ²)	°F	°C		Without Thermocouple	Standard Type K Thermocouple	Low Noise Type K Thermocouple
500	120	Yellow to Orange	11.9	1.9	796	424	4.15	CRL20021	—	CRL20022
500	220-240	Rose to Grey	11.9	1.9	796	424	4.15	CRL10009	CRL10010	—
500	220-240	White	11.9	1.9	796	424	4.15	CRL00009	CRL00010	—
500	240/480	Yellow to Orange	11.9	1.9	796	424	4.15	CRL20023	—	CRL20024
750	120/240	Yellow to Orange	17.9	2.8	956	513	3.68	CRL20025	—	CRL20026
750	220-240	Rose to Grey	17.9	2.8	956	513	3.68	CRL10011	CRL10012	—
750	220-240	White	17.9	2.8	956	513	3.68	CRL00011	CRL00012	—
750	240/480	Yellow to Orange	17.9	2.8	956	513	3.68	CRL20027	—	CRL20028
950	220-240	Rose to Grey	22.7	3.5	1053	567	3.45	CRL10001	CRL10002	—
950	220-240	White	22.7	3.5	1053	567	3.45	CRL00001	CRL00002	—
1000	220-240	Rose to Grey	23.9	3.7	1076	580	3.40	CRL10013	CRL10014	—
1000	220-240	White	23.9	3.7	1076	580	3.40	CRL00013	CRL00014	—
1000	240/480	Yellow to Orange	23.9	3.7	1076	580	3.40	CRL20029	—	CRL20030
1150	220-240	Rose to Grey	27.5	4.3	1145	618	3.25	CRL10003	CRL10004	—
1150	220-240	White	27.5	4.3	1145	618	3.25	CRL00003	CRL00004	—
1250	240/480	Yellow to Orange	29.9	4.6	1191	644	3.16	CRL20031	—	CRL20032
1400	480	Rose to Grey	33.5	5.2	1262	683	3.03	CRL10015	CRL10016	—
1400	480	White	33.5	5.2	1262	683	3.03	CRL00015	CRL00016	—
1500	240/480	Yellow to Orange	35.9	5.6	1308	709	2.95	CRL20033	—	CRL20034
1600	480	Rose to Grey	38.2	5.9	1351	733	2.88	CRL10017	CRL10018	—
1600	480	White	38.2	5.9	1351	733	2.88	CRL00017	CRL00018	—
1800	480	Rose to Grey	43.0	6.7	1418	770	2.78	CRL10019	CRL10020	—
1800	480	White	43.0	6.7	1418	770	2.78	CRL00019	CRL00020	—

NOTES: All dual voltage heaters have two windings (parallel connected for the lower voltage & series connected for the higher voltage). Single voltage heaters are single winding designs.

Units with an internal “low noise” style thermocouple have 12" leads (see page 7-14). Standard type “K” T/C units also available.

Heaters with yellow to orange color are exact replacements for heaters in CRP Modular 12 × 12 CRP Radiant Panels on page 7-24.

* **Watt density**
calculated using heater face surface area.

** **E-Mitter heater body temperature**
as measured with internal thermocouple when mounted facedown in stock CRK reflector and operating in 72°F (22°C) room ambient.

*** **Peak infrared radiation wavelength** as calculated from Wien's Law, for operating temperature shown. Expressed in microns (μm).


Custom Heater Assemblies & Power Control Panels



Type CRA Custom Linear Arrays
start on page 7-18



Type ARA Custom Structural Arrays
start on page 7-28



Array Power/Temperature Control Panels (see page 7-37)

(800) 323-6859 • Email: sales@tempco.com