



### Worksheet for Sealed IR Quartz Lamps

#### Ordering Information

To process your order please specify the following information.

#### 1.) Heater Specifications:

- Filament Temperature:  Standard FRMW = 1500K  High Temperature FRMW = 1900K  
 Standard Halogen = 2500K  NIR Halogen = 2900K  Other \_\_\_\_\_
- Tube Cross Section:  Single Round Tube  Twin Bore Tube
- Tube Shape  Straight  Special Bend Configuration
- Tube Color:  Clear (Standard)  Ruby  Translucent  Frosted Ruby  Frosted (Sandblasted) Clear
- Maximum Overall Length (Inches) \_\_\_\_\_
- Heated Length (Inches) \_\_\_\_\_
- Built-In Reflector:  No Reflector  White Reflector  Gold Reflector

#### 2.) Electrical requirements:

- Voltage:  120  240  277  480  Other \_\_\_\_\_
- Wattage \_\_\_\_\_

#### 3.) Termination Types:

- Single Tube Bases  R7s  R7W  RC  X  F  FX  U  Other \_\_\_\_\_
- Twin Tube Bases  Ceramic with straight exit leads (Standard)  Other \_\_\_\_\_
- Lead Wire Type  Bare Wire (Standard)  Teflon®@200°C  Fiberglass@250°C  Mica@450°C
- Lead Length 5.7" (Standard)\_\_\_\_\_ (Note: Type R7s and X do not have leads)
- Terminal Options  None (Standard)  #10 Ring Terminal  #10 Spade Terminal  Other \_\_\_\_\_

#### 4.) Panel wiring & control options:

- Tempco to supply array panel
- Factory wired per customer specs & wiring diagram
- Tempco Engineering to design internal wiring & determine line input requirements
- Tempco to supply turnkey power control panel(s)

5.) Any special features required? \_\_\_\_\_

#### 6.) Application Data:

Type of application and physical properties of processed materials

\_\_\_\_\_

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**(800) 323-6859 • Email: [sales@tempco.com](mailto:sales@tempco.com)**