


### Series CRC Curved Face Ceramic E-Mitters – Size: 60 mm × 122 mm (2.36" × 4.80")



Color shown is rose (cold) to grey (hot)

#### Optional Features

- \* Additional Power or Thermocouple Lead Lengths (page 7-23)
- \* Two-Piece Wave Mounting Clip (page 7-14)
- \* Reflectors and Other Accessories (pages 7-20 through 7-23)
- \* Arrays and Power/Temperature Control Panels (start on page 7-15)

#### Standard (Non-Stock) CRC E-Mitters

E-Mitters listed have 3.50" ceramic bead insulated leads, #8-10 spade terminals, and a one-piece spring clip for mounting.

Wattage	Voltage	Color	Watt Density*		Heater Body Temp.**		Part Number	
			(W/in <sup>2</sup> )	(W/cm <sup>2</sup> )	(Typical Operating) °F	°C	Without Thermocouple	With Type K Thermocouple
125	220/240	Rose to Grey	10.80	1.67	756	402	CRC10005	CRC10007
125	220/240	White	10.80	1.67	756	402	CRC00005	CRC00007
200	220/240	Rose to Grey	17.27	2.68	942	506	CRC10013	CRC10015
200	220/240	White	17.27	2.68	942	506	CRC00013	CRC00015
325	120	Rose to Grey	28.07	4.35	1156	624	CRC10018	CRC10020
325	120	White	28.07	4.35	1156	624	CRC00018	CRC00020
325	220/240	Rose to Grey	28.07	4.35	1156	624	CRC10021	CRC10023
325	220/240	White	28.07	4.35	1156	624	CRC00021	CRC00023
325	480	Rose to Grey	28.07	4.35	1156	624	CRC10064	CRC10140
325	480	White	28.07	4.35	1156	624	CRC00064	CRC00140
500	120	Rose to Grey	43.18	6.69	1420	771	CRC10024	CRC10026
500	120	White	43.18	6.69	1420	771	CRC00024	CRC00026
500	220/240	Rose to Grey	43.18	6.69	1420	771	CRC10027	CRC10029
500	220/240	White	43.18	6.69	1420	771	CRC00027	CRC00029
500	480	Rose to Grey	43.18	6.69	1420	771	CRC10066	CRC10141

### Semi-Finished Stock CRC E-Mitters (Five Business Day Manufacturing)

Semi-Finished Series CRC E-Mitters listed below are stocked ready for color glazing. Colors available are metamorphing rose (cold) to grey (hot), traditional white, metamorphing yellow (cold) to orange (hot), and black.

They can be terminated with beaded leads up to 6" long with spliced-on lead wire for lengths beyond 6" and straight, ring, or spade terminals. Some are available with a thermocouple (any length).

A part number will be assigned at time of order.

Wattage	Voltage	Watt Density*		Heater Body**		Optional Thermocouple (Any Length)
		(W/in <sup>2</sup> )	(W/cm <sup>2</sup> )	Temperature (Typical) °F	°C	
200	230	17.27	2.68	942	506	Type K
325	230	28.07	4.35	1156	624	Type K
325	480	28.07	4.35	1156	624	N/A
500	230	43.18	6.69	1420	771	Type K
500	480	43.18	6.69	1420	771	N/A

**CRC Ordering Information** (See page 7-2)

**CONTINUED** 